RACK CONVEYOR

D832LTDD



Electronic rack conveyor dishwasher - 27

SEE MORE TECHNICAL DATA:

Max productivity (basket/hour)	135-200-270

HIDE THE OTHER TECHNICAL DATA:

External dimensions - WxDxH (cm)	252x77x162
Hot water Power (kW)	31,5
Cold water Power (kW)	41,5
Cold water Power with regenerator (kW)	36,5
Washing pump capacity (kW)	900
Prewashing pump capacity (kW)	400
Water consumption rinsing (lt/hour)	240
Drying-power (kW)	6
Drying-fan capacity (m3/hour)	1400
Supply (N)	400V 3N 50Hz
Weight (kg)	510
Volume (m3)	3.59
Power (kW)	26,4

Savings on operational costs, great efficiency, hygiene, flexibility and total control: these are the dreams that come true with the highly advanced Domina Tetra and MonoRinse technology.
The IdroWash plus wash system with its constant flow spray arms insures the best absorbed power use without unuseful load waste. The washing cycle becomes quicker despite less powerful pumps, thus reducing energy consumption.







* USEFUL WIDTH FOR BASKET

** USEFUL HEIGHT FOR BASKET

A	Ø 1"1/2 M	D	Ø PG11	End switch			
A1	Ø 31 M	E	Ø 250	Steam exaust			
B 50°C	G 3/4" M	F	Ø 14 M	Detergent inlet			
B1 10°C	G 3/4" M	G	Ø 7 M	Rinse aid inlet			
C	PG36 Power supply	H	Ø 6	Equipotential	L	Ø 250	Dryer suction

Installation layout	Rack Type	T202S	00
Designed by: M.PUCCI	Date: 15.05.2015	Denomination :	Code : Rev.1